

### Output Ratings

Generating Set Model	P675P5	P750E5
-	-	-
480V, 60 Hz	675.0 kVA 540.0 kW	750.0 kVA 600.0 kW

Ratings at 0.8 power factor.

### Ratings Definitions

#### Prime Power - Model P675P5

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

#### Standby Power - Model P750E5

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

### Technical Data

<b>Engine Make &amp; Model:</b>	Perkins 2806A-E18TAG3	
<b>Alternator Model:</b>	LL7024J	
<b>No. of Cylinders/Alignment:</b>	6 / In Line	
<b>Displacement: litres (cu.in)</b>	18.1 (1104.5)	
<b>Bore/Stroke: mm (in)</b>	145.0 (5.7)/183.0 (7.2)	
<b>Compression Ratio:</b>	14.5:1	
<b>Induction:</b>	Turbocharged Air To Air Charge Cooled	
<b>Frequency:</b>	50 Hz	60 Hz
<b>Engine Speed:</b>	-	1800 RPM
<b>Gross Engine Power: kW (hp)</b>	-	678.2 (909.0)
<b>BMEP: kPa (psi)</b>	-	2494.0 (361.7)
<b>Piston Speed: m/sec (ft/sec)</b>	-	11.0 (36.1)
<b>Fuel Tank Capacity: litres (US gal)</b>	-	1000 (264.2)
<b>Fuel Consump, l/hr (USg/hr) P675P5</b>	-	138.4 (36.6)
<b>Fuel Consump, l/hr (USg/hr) P750E5</b>	-	155.6 (41.1)
<b>Heat Rejected to Exhaust System: kW (Btu/min)</b>	-	524.4 (29822)
<b>Heat Rejected to Water &amp; Lube Oil: kW (Btu/min)</b>	-	170.9 (9719)
<b>Heat Radiation to Room: kW (Btu/min)</b>	-	45.6 (2593)
<b>Exhaust Gas Temperature: °C (°F)</b>	-	542 (1008)
<b>Radiator Cooling Air Flow: m<sup>3</sup>/min (cfm)</b>	-	804.0 (28393)
Cooling system designed to operate in ambient conditions up to 50°C (122°F)*		
<b>Combustion Air Flow: m<sup>3</sup>/min (cfm)</b>	-	47.6 (1681)
<b>Exhaust Gas Flow: m<sup>3</sup>/min (cfm)</b>	-	143.0 (5050)

\* Contact your local FG Wilson dealer for power ratings at specific site conditions.

### Dimensions and Weights

Length: mm (in)	Width: mm (in)	Height: mm (in)	Dry: kg (lb)	Wet: kg (lb)
4111 (161.9)	1536 (60.5)	2246 (88.4)	4905 (10814)	4975 (10968)

Dry = With Lube Oil    Wet = With Lube Oil and coolant

Ratings in accordance with ISO 8528, ISO 3046, IEC 60034, BS5000 and NEMA MG-1/22.  
Generating set pictured may include optional accessories.



www.3tech.net



P675P5 / P750E5



**3Tech Corporate Limited**  
Unit 904, 9/F., Fu Hang Industrial Building,  
1 Hok Yuen Street East, Hung Hom,  
Kowloon, Hong Kong.  
Tel: +852-2766 9787 Fax: +852-2766 9774  
Email:sales@3tech.net

Headquarters: Hong Kong    China: Beijing, Dongguan, Shenzhen, Xiamen  
Overseas: Nigeria, D.R.Congo, Ghana, Kenya, Tanzania, Pakistan, USA, Canada, France



ISO 9001:2008  
Certificate No.194845

