



www.3tech.net

**Output Ratings**

Generating Set Model	P730P1	P800E1
380-415V, 50 Hz	730.0 kVA 584.0 kW	800.0 kVA 640.0 kW
480V, 60 Hz	750.0 kVA 600.0 kW	844.0 kVA 675.2 kW

Ratings at 0.8 power factor.

**Ratings Definitions**

**Prime Power - Model P730P1**

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

**Standby Power - Model P800E1**

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).



**Technical Data**

Engine Make & Model:	Perkins 4006TAG2A	
Alternator Model:	LL7024L	
No. of Cylinders/Alignment:	6 / In Line	
Displacement: litres (cu.in)	22.9 (1398.7)	
Bore/Stroke: mm (in)	160.0 (6.3)/190.0 (7.5)	
Compression Ratio:	13.6:1	
Induction:	Turbocharged Air To Air Charge Cooled	
Frequency:	50 Hz	60 Hz
Engine Speed:	1500 RPM	1800 RPM
Gross Engine Power: kW (hp)	711.0 (953.0)	759.0 (1018.0)
BMEP: kPa (psi)	2481.0 (359.9)	2208.0 (320.2)
Piston Speed: m/sec (ft/sec)	9.5 (31.2)	11.4 (37.4)
Fuel Tank Capacity: litres (US gal)	1494 (394.7)	1494 (394.7)
Fuel Consump, P730P1 l/hr (USg/hr)	149.8 (39.6)	167.0 (44.1)
Fuel Consump, P800E1 l/hr (USg/hr)	163.4 (43.2)	189.1 (50.0)
Heat Rejected to Exhaust System: kW (Btu/min)	499.0 (28378)	680.0 (38671)
Heat Rejected to Water & Lube Oil: kW (Btu/min)	230.0 (13080)	243.0 (13819)
Heat Radiation to Room: kW (Btu/min)	88.7 (5044)	98.9 (5624)
Exhaust Gas Temperature: °C (°F)	430 (806)	430 (806)
Radiator Cooling Air Flow: m³/min (cfm)	1134.0 (40047)	1326.0 (46827)
Cooling system designed to operate in ambient conditions up to 50°C (122°F)*		
Combustion Air Flow: m³/min (cfm)	71.0 (2507)	73.0 (2578)
Exhaust Gas Flow: m³/min (cfm)	180.0 (6357)	190.0 (6710)

\* Contact your local FG Wilson dealer for power ratings at specific site conditions.

**Dimensions and Weights**

Length: mm (in)	Width: mm (in)	Height: mm (in)	Dry: kg (lb)	Wet: kg (lb)
4280 (168.5)	1912 (75.3)	2277 (89.6)	6059 (13358)	6170 (13603)

Dry = With Lube Oil    Wet = With Lube Oil and coolant

Ratings in accordance with ISO 8528, ISO 3046, IEC 60034, BS5000 and NEMA MG-1/22. Generating set pictured may include optional accessories.

P730P1 / P800E1



**3Tech Corporate Limited**  
 Unit 904, 9/F., Fu Hang Industrial Building,  
 1 Hok Yuen Street East, Hung Hom,  
 Kowloon, Hong Kong.  
 Tel: +852-2766 9787 Fax: +852-2766 9774  
 Email:sales@3tech.net

Headquarters: Hong Kong    China: Beijing, Dongguan, Shenzhen, Xiamen  
 Overseas: Nigeria, D.R.Congo, Ghana, Kenya, Tanzania, Pakistan, USA, Canada, France



ISO 9001:2008  
 Certificate No.194845

